


Main Specification			
Magnification	0.15X	0.2X	0.25X
Working Distance	860±5	654.8±5	538±5
Image Distance	86.58±2.5	92.82±2.5	98.81±2.5
Conjugate Distance	1026.7±9	827.8±9	717.1±9
Flange Focal Distance	117.0	123.5	129.2
Max image	φ66		
F/#	4.5		
EFL	100		
FOV	34.6°		
ENP Diameter	23		
Distortion	0.005%		
IMAGE QUALITY			
AXIS	φ46.2	φ66	
160lp/mm	125lp/mm	100lp/mm	

Image space NA	0.082
Object space NA	0.017
Entrance pupil diameter	23
Entrance pupil position	36.06
Exit pupil diameter	30.52
Exit pupil position	-184.56

注：
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE:
LINEARITY TOLERANCES ±0.05
ANGULAR TOLERANCES ARE ±30°
DRAFT ANGLES AREA ±0.5°/SIDE



材料(环保)	单位	比例
	mm	1:1

设计	朱周德	2016-06-22
校对		
审核		
批准		

名称	LS0802A技术规格图	页码	1/1
代号	LS0802A-SPEC	版本	V0

标记	处数	更改文件号	担当	变更日期
----	----	-------	----	------