


Main Specification

Magnification	0.29X	0.33X	0.4X	Image space NA	0.078
Working Distance	465±5	415.1±5	351.2±5	Object space NA	0.026
Image Distance	99.55±2.5	104.33±2.5	112.78±2.5	Entrance pupil diameter	23.37
Conjugate Distance	644.85±9	599.7±9	544.58±9	Entrance pupil position	36.3
Flange Focal Distance	130.1	134.9	143.4	Exit pupil diameter	30.93
Max image		φ62		Exit pupil position	-197.88
F/#		4.5			
EFL		116			
FOV		29°			
ENP Diameter		23.37			
Distortion		<0.005%			

注：
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE :
LINEARITY TOLERANCES ±0.05
ANGULAR TOLERANCES ARE ±30°
DRAFT ANGLES AREA ±0.5°/SIDE



材料(环保) 单位 比例
mm 1:1

IMAGE QUALITY

AXIS	φ46.2	φ66
------	-------	-----

设计	朱周德	2017-03-28	名称	LS1203A技术规格图	页码
校对					1/1
审核			代号	LS1203A-SPEC	版本
批准					V0
标记	处数	更改文件号	担当	变更日期	