


Main Specification			
Magnification	0.9X	1.0X	1.1X
Working Distance	176.7±5	164.2±5	153.7±5
Image Distance	144.8±2.5	156.11±2.5	167.67±2.5
Conjugate Distance	401.8±9	400.56±9	401.67±9
Flange Focal Distance	175.4	186.7	198.3
Max image		φ62	
F/#		4.5	
EFL		116	
FOV		28°	
ENP Diameter		25.6	
Distortion		<0.05%	
IMAGE QUALITY			
AXIS	φ46.2	φ66	

Image space NA	0.062
Object space NA	0.062
Entrance pupil diameter	25.63
Entrance pupil position	38.63
Exit pupil diameter	30.93
Exit pupil position	-249.65

注：  
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE :  
LINEARITY TOLERANCES ±0.05  
ANGULAR TOLERANCES ARE ±30°  
DRAFT ANGLES AREA ±0.5°/SIDE



材料(环保) 单位 比例  
mm 1:1

设计	朱周德	2017-03-30	名称	LS1210A技术规格图	页码
校对					
审核			代号	LS1210A-SPEC	版本
批准					

	1	朱周德	2017,06,19	审核	
标记	处数	更改文件号	担当	变更日期	批准