


Main Specification

Magnification	1.29X	1.24X	1.19X	Image space NA	0.051
Working Distance	146.2±5	149.9±5	154±5	Object space NA	0.064
Image Distance	212.56±2.5	206.8±2.5	200.62±2.5	Entrance pupil diameter	29.75
Conjugate Distance	436.67±9	434.66±9	432.54±9	Entrance pupil position	81.85
Flange Focal Distance	237.9	232.2	226	Exit pupil diameter	26.08
Max image		$\phi 62$		Exit pupil position	-252.86
F.No		4.5			
EFL		116			
FOV		20.88°			
ENP Diameter		29.75			
Distortion		<0.005%			

注：
Logo上的圆点粘贴位置与成像面垂直表示最佳成像点。

TOLERANCE :
LINEARITY TOLERANCES ±0.05
ANGULAR TOLERANCES ARE ±30'
DRAFT ANGLES AREA ±0.5°/SIDE



材料(环保) 单位 比例
- MM 1:1

IMAGE QUALITY

AXIS	$\phi 46.2$	$\phi 66$
------	-------------	-----------

设计		名称	LS1212A规格书	页码	1/1
校对		代号	LS1212A-SPEC	版本	V0
审核					
批准					
标记	处数	更改文件号	担当	变更日期	