



Main Specification				Image space NA	0.08
Magnification	-0.22	-0.26	-0.30	Object space NA	0.02
Working Distance	767.64 ± 5	663.34 ± 5	587.64 ± 5	Entrance pupil diameter	30.66
Conjugate Distance	969.75 ± 9	874.3 ± 9	804.5 ± 9	Entrance pupil position	54.44
Flange Focal Distance	155.15	160.95	166.85	Exit pupil diameter	29.95
Max image circle	$\phi 82$			Exit pupil position	-182.3

注：notes 贴付位置与最佳成像方向垂直。

F/#	3.8-16			TOLERANCE: LINEARITY TOLERANCES ± 0.05 ANGULAR TOLERANCES ARE $\pm 30'$ DRAFT ANGLES AREA $\pm 0.5^\circ$ /SIDE				三角法	材料(环保)	单位	比例			
EFL	116									mm	1:1			
Distortion	0.001%													
Structure	8G													
IMAGE QUALITY														
AXIS	$\phi 46.2$	$\phi 66$	$\phi 82$					设计	CHP	2014-12-23	名称	LS1626B技术规格图	页码	1/1
200lp/mm	160lp/mm	160lp/mm	125lp/mm					校对			代号	LS1626B-SPEC	版本	V0
				标记	处数	更改文件号	担当	变更日期	批准					