



Main Specification

Magnification	0.04 X	0.167X	0.33 X
Working Distance	1557.4±5	404.4±5	218.97±5
Image Distance	40.49±2.5	48.07±2.5	58.24±2.5
Conjugate Distance	1641.73±9	496.32±9	321.05±9
Flange Focal Distance	55.73±0.5	63.31±0.5	73.48±0.5
EFL	60		
Max image	ø64		
F/#	4		
Distortion	0.6%	0.19%	0.12%
FOV	1591.2	386.92	192.5
Illumination	45%		

H ₁	15.78
H ₂	-70.8
Entrance Pupil Position	17.33
Exit Pupil Position	-69.29

IMAGE QUALITY		
AXIS	ø45	ø64
80lp/mm	50lp/mm	40lp/mm

					TOLERANCE: LINEARITY TOLERANCES ±0.05 ANGULAR TOLERANCES ARE±30' DRAFT ANGLES AREA±0.5°/SIDE		三角法	材料(环保)	单位	比例
									mm	1:1
					设计	朱周德	2014-08-15	名称	LS6016A技术规格图	
					校对				页码	1/1
					审核			代号	LS6016A-SPEC	
					批准				版本	V1
	1			朱周德	2018,01,16					
标记	处数	更改文件号	担当	变更日期						