


Main Specification				Image space NA	0.1
Magnification	0.14X	0.1X	0.08X	Object space NA	0.01
Working Distance	722±5	992.4±5	1229.2±5	Entrance pupil diameter	21.58
Conjugate Distance	856.86±9	1123.5±9	1358.34±9	Entrance pupil position	42.87
Flange Focal Distance	87±0.5	82.7±0.5	81.3±0.5	Exit pupil diameter	22.27
Max image circle	$\phi 64$			Exit pupil position	-107.16
F/#	4.0-16				
EFL	90				
Distortion	0.01%				
IMAGE QUALITY					
AXIS	$\phi 46.2$	$\phi 66$			
200lp/mm	125lp/mm	125lp/mm			

注：
Logo上的圆点粘贴位置与成像面垂直为最佳成像点。

TOLERANCE:
LINEARITY TOLERANCES ±0.05
ANGULAR TOLERANCES ARE ±30'
DRAFT ANGLES AREA ±0.5°/SIDE



材料(环保) 单位 比例
mm 1:1

设计	朱周德	2016-11-24	名称	LS9001A技术规格图	页码	1/1
校对			代号	LS9001A-SPEC	版本	V0
审核						
批准						

标记	处数	更改文件号	担当	变更日期
----	----	-------	----	------