



1.1" F 1:2.8 /25C Mount										
EFL	25mm									
F No.	2.8~16(±10%)									
Flange back Mount	17.526mm									
Mount	C-Mount									
Distortion (TV)	126~314.1mm									
Storage Temperature Range	<0.07%									
Working distance	-20~+60°C									
Magnification	1.1"(φ17.6)		1"(φ16)		2/3"(φ11)					
	H	V	H	V	H	V				
FOV(mm)	65	-0.4X	35	26	32	24	22	16.5		
	74.4	-0.35X	40	30	35.6	27.4	25	18.8		
	85.4	-0.3X	47	35	42.6	32	29	22		
	103.4	-0.25X	56	42	51	38	35	26		
	125.4	-0.2X	70	52.8	64	48	44	33		
173.4	-0.15X	93	70	85	64	58.6	44			
260.4	-0.1X	140	105	128	96	88	66			

△4	1				2017-09-27	设计	三角法	材料(环保)	ML2510A规格书	单位	比例
△3	1				2017-09-11	设计	三角法			mm	2.5:1
△2	1				2017-08-22	校对	三角法				页码
△1	1				2017-08-07	审核	三角法				1/1
标记	处数	更改文件号	担当	变更日期	批准				ML2510A-SPEC		版本
											V4

TOLERANCE:
 LINEARITY TOLERANCES ±0.05
 ANGULAR TOLERANCES ARE±30'
 DRAFT ANGLES AREA±0.5°/SIDE

