



1.1" F 1:2.8 /50 C Mount

EFL	50mm						
F No.	2.8~16(±10%)						
Flange back Mount	17.526mm						
0/1	C-Mount						
Distortion (TV)	195.6~220.1mm						
Storage Temperature Range	<0.05%						
	-20~+60°C						
Working distance	Optical Magnification	FOV(mm)		2/3" (φ11)			
		1.1"(φ17.6)	1"(φ16)	H	V	H	V
95.4	-0.8X	17.5	13	15.9	11.9	11	8.2
99.4	-0.75X	18.6	14	16.9	12.7	11.7	8.8
103.4	-0.7X	20	15	18.2	13.6	12.6	9.4
109.4	-0.65X	21.5	16.1	19.6	14.7	13.6	10.2
115.4	-0.6X	23.3	17.6	21.2	15.9	14.7	11
123.4	-0.55X	25.5	19.1	23.1	17.3	16	12
132.4	-0.5X	28	21	25.4	19	17.6	13.2

4	1			2017-09-27	设计	审核	批准	材料(环保)	ML5010A规格书	单位	比例
3	1			2017-09-11	设计	校对			ML5010A规格书	mm	2:1
2	1			2017-08-07	校对						页码
1	1			2017-06-22	审核						1/1
					变更日期				ML5010A-SPEC		版本
					变更文件号						V4
					担当						
					处数						
					标记						

TOLERANCE:
LINEARITY TOLERANCES ±0.05
ANGULAR TOLERANCES ARE±30'
DRAFT ANGLES AREA±0.5°/SIDE



名称
ML5010A规格书

材料(环保)
ML5010A-SPEC

单位
mm

比例
2:1

页码
1/1

版本
V4