



1.1" F 1:3.8 /75 C Mount

EFL	75mm						
F No.	3.8~16($\pm 10\%$)						
Flange back Mount	17.526mm C-Mount						
0/I	357~557mm						
Distortion (TV)	<0.05%						
Storage Temperature Range	-20~+60°C						
Working distance	1.1"($\phi 17.6$)		1"($\phi 16$)		2/3" ($\phi 11$)		
	H	V	H	V	H	V	
257	-0.38X	37.05	27.78	33.68	25.26	23.15	17.36
282	-0.337X	41.78	31.33	37.98	28.48	26.11	19.58
307	-0.302X	46.62	34.96	42.38	31.78	29.13	21.85
332	-0.274X	51.38	38.54	46.71	35.03	32.11	24.08
357	-0.25X	56.32	42.24	51.2	38.4	35.2	26.4
382	-0.231X	60.95	45.71	55.41	41.55	38.09	28.57
407	-0.214X	65.79	45.71	59.81	44.85	41.12	30.84
432	-0.2X	70.4	52.8	64	48	44	33
457	-0.186X	75.69	56.77	68.81	51.61	47.31	35.48
471	-0.18X	78.22	58.66	71.11	53.33	48.88	36.66

TOLERANCE: LINEARITY TOLERANCES ± 0.05 ANGULAR TOLERANCES ARE $\pm 30'$ DRAFT ANGLES AREA $\pm 0.5^\circ$ SIDE		三棱法		材料(环保)		单位	
设计		校对		ML7510A规格书		mm	
1		---		CHP		2:1	
2		---		CHP		页码	
更改文件号		2017-09-11		2017-08-04		1/1	
担当		审核		批准		版本	
变更日期		2017-08-04		批准		V2	
批准							